

Material Safety Data Sheet

Revision Date: 2/26/10

NA = Not Applicable NE = Not Established

Section 1. General Information

Product name: **Octoblen**
Chemical Family: Aqueous Acrylic Emulsion
Manufacturer: **IPA Systems, Inc.**
2745 North Amber Street, Philadelphia, Pa. 19134
Phone: 800-523-3834 • 215-425-6607
Fax: 215-425-6234
E-mail: info@ipasystems.com
Website: www.ipasystems.com

Emergency Phone Number - Chemtrec: 800-424-9300

Section 2. Hazardous Ingredients

<u>Name:</u>	<u>C.A.S. No.</u>	<u>Percent</u>	<u>Threshold Limit Value (units)</u>
Acrylic Latex Emulsion	NA	30 - 70	Not hazardous

Section 3. Physical Data

Boiling Point: 212°F (100°C) Specific Gravity: (H₂O = 1): 1.03
Vapor Pressure (mm Hg.): 17 mm Hg @ 20°C Percent Volatile by Volume: NE
Vapor Density (Air = 1): 1 Evaporation Rate (B_{Ac} = 1): 1
Solubility in Water: Dilutable pH: 9.3
Appearance and Odor: White liquid, slight odor

Section 4. Fire and Explosion Hazard Data

Flash Point: Noncombustible
Autoignition Temperature: NA
Flammable Limits: LEL = NA UEL = NA
Extinguishing Media: Use extinguishing media appropriate for surrounding fire.
Special Fire Fighting Procedures: NA
Unusual Fire and Explosion Hazards: Material can splatter above 212°F (100°C). Polymer film can burn.

Material Safety Data Sheet

Revision Date: 2/26/10

NA = Not Applicable NE = Not Established

Section 5. Health Hazard Data

OSHA Permissible Exposure Limit: NA

ACGIH Threshold Limit Value: NA

Carcinogen – NTP Program: No

Carcinogen – IARC Program: No

Symptoms of Exposure:

Skin: Irritating on prolonged or repeated contact.

Eye contact: Can cause eye irritation.

Inhalation: Can cause headache, nausea, irritation of nose, throat and lungs.

Medical Conditions Aggravated by Exposure: NE

Routes of Entry: Ingestion, Inhalation, Skin Contact, Eye Contact

Emergency and First Aid Procedures:

Inhalation: Move subject to fresh air.

Swallowing: Dilute by giving 2 glasses of water to drink. Seek medical attention.

Eye Contact: Immediately flush well with large amounts of water for 15 minutes. Seek medical attention.

Skin Contact: Wash thoroughly with soap and water.

Section 6. Reactivity Data

Stability: Stable

Conditions to Avoid: Freezing or temperatures above 350°F (177°C)

Incompatibility (Materials to Avoid Contact): None known

Hazardous Decomposition or By-Products: Thermal decomposition may yield acrylic monomers.

Hazardous Polymerization: Will not occur.

Section 7. Procedures for Safe Handling and Use

Spill Response: Keep spectators away. Floor may be slippery; use care to avoid falling. Contain spills immediately by diking with inert material (e.g., sand, earth). Transfer liquid and solid diking material to separate suitable containers for recovery or disposal. Keep spills and cleaning runoffs from entering municipal sewers or open bodies of water.

Waste Disposal Method: Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant liquid and flush to a chemical sewer. Incinerate liquid and contaminated solids according to federal, state and local regulations.

Material Safety Data Sheet

Revision Date: 2/26/10

NA = Not Applicable NE = Not Established

Section 8. Control Measures

Eye Protection: Wear chemical splash goggles (ANSI Z87.1 or approved equivalent).

Respiratory Protection: Wear MSHA/NIOSH half-mask dust/mist when mist occurs.

Skin Protection: Wear neoprene gloves.

Ventilation: Local exhaust, minimum capture velocity 100 ft/min.

Other Protection: Eyewash facility

Section 9. Special Precautions

Keep from freezing; material may coagulate.

Precautions for Repair and Maintenance of Contaminated Equipment: NA

Other Precautions: NA