



IPA SYSTEMS

Enviro-Form Release

Economical, Biodegradable, Form Release



IPA SYSTEMS

QUALITY PRODUCTS FOR THE CONCRETE /MASONRY REPAIR INDUSTRY

Description

Enviro-Form Release is an economical, biodegradable, V.O.C compliant concrete form release. Enviro-Form Release works to ensure a clean release on plywood, aluminum, steel, fiberglass and other concrete forming materials. Enviro-Form Release acts as an adhesion barrier for the concrete while minimizing surface dusting. Applied correctly, Enviro-Form Release will not stain concrete or interfere with the adhesion of coatings.

Advantages

- ◆ Made in America
- ◆ Economical, easy to use
- ◆ Zero V.O.C.'s
- ◆ Biodegradable
- ◆ Minimizes dusting
- ◆ Water clean-up

Coverage

Estimated Coverage:

Hard/dense/smooth forms (plastic, fiberglass, steel, HDO, aluminum)

1000 – 1500 sq. ft./gal. (24.6 - 36.9 sq m/L)

Medium density overlaid plywood

1000 – 1250 sq. ft./gal. (24.6 - 30.7 sq m/L)

Dimensional or rough lumber, striated plywood

500 – 1000 sq. ft./gal. (12.3 - 24.6 sq m/L)

Apply 2 coats @ 500 sq ft /gal (12.3 sq m/L) on new forms,

then 1000 sq ft /gal (24.6 sq m / L) on subsequent treatments

Note: Texture and surface absorption of forming material will influence final coverage rates.

Packaging

Available in 5 gallon (18.93 L) and 55 gallon (208.18 L) containers.

Storage: Keep from freezing. Store in original containers, keeping container lids, spouts and/or bungs tightly sealed. Shelf life of 12 months in properly stored sealed containers.

Application

Surface Preparation: Surfaces to be treated should be clean and free of all water, dust and dirt or residues, which might transfer to the final concrete surface. Stir well prior to use. Apply during dry weather with low-pressure spray, roller or brush. Apply uniformly to assure proper coverage. Use of a fine fan tip, 0.1-0.2 gpm allows for more even coverage and avoidance of excess material. Wipe excess material from forms prior to form construction and concrete placement.

FOR BEST RESULTS APPLY TO FORMS BEFORE EACH USE.

Limitations

FOR PROFESSIONAL USE ONLY

Forms and equipment must be clean and dry prior to use. Excessive rain after application prior to concrete placement may require re-application. When properly treated forms should have a uniform thin film, with a slight waxy feel. After use, a white residue may be visible on forms. This is normal for water based form release agents and should not be confused with concrete build up.

Clean-up

Use clean water for clean up.

IPA SYSTEMS, INC

P.O. Box 26869- 2745 North Amber Street, Philadelphia, PA 19134

Tel: 800-523-3834, Fax: 215-425-6234, E-mail: info@ipasystems.com, Web Site: www.ipasystems.com



IPA SYSTEMS



IPA SYSTEMS

QUALITY PRODUCTS FOR THE CONCRETE /MASONRY REPAIR INDUSTRY

Caution

Use with adequate ventilation, Wear protective clothing, gloves and eye protection (Goggles, Safety Glasses and/or Face Shield) Do not take internally: In case of ingestion, seek medical help immediately. May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed. If eye contact occurs, flush immediately with clean water and seek medical help as needed. Dispose of waste material in accordance with federal, state and local requirements.

Keep out of the reach of children

For more information: Refer to MSDS prior to using this product.

Warranty

This product is warranted and guaranteed to be of good quality. Manufacturer, as its sole and exclusive liability hereunder, will replace material if proved defective. This warranty and guarantee are expressly in lieu of all others, express or implied, including any implied warranty of merchantability or fitness for a particular purpose and may not be extended by representatives or any persons, written sales information, or drawing in any manner whatsoever. While the manufacturer recommends uses for the product based on tests believed reliable, no warranties, express or implied, or guarantee can be given as to particular methods of use or application, nor can performance be warranted, expressly or impliedly, or guaranteed under special conditions. Distributors, salesperson or company representatives are not authorized to extend or vary any warranties or guarantees beyond those outlined herein nor may the manufacturer's or seller's limitation of liability be waived or altered in any manner whatsoever.

IPA SYSTEMS, INC

P.O. Box 26869- 2745 North Amber Street, Philadelphia, PA 19134

Tel: 800-523-3834, Fax: 215-425-6234, E-mail: info@ipasystems.com, Web Site: www.ipasystems.com
